Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A method of routing a flow of frames comprising: applying a correspondence between at least some a plurality of logical ports and a plurality of physical ports of a switch, at least one logical port having corresponded a plurality of physical ports to form a trunked group, wherein said corresponded physical ports can be any of said plurality of physical ports exiting said switch and wherein frames in a trunked group are delivered in order; and

balancing frame traffic through said switch using said plurality of logical ports, said frame traffic including frames exiting said switch via said physical ports, a selected physical port for at least one of said frames exiting said switch being selected based at least in part on said correspondence, with any frames exiting said switch via physical ports forming a trunked group being balanced over said physical ports forming the trunked group.

(Original) The method of claim 1, wherein a selected physical port for each
of said frames exiting said switch is selected based at least in part on said
correspondence.

3.-5. (Cancelled)

6. (Currently Amended) The method of claim 31, wherein said balancing comprises applying a pseudo-random process to select a particular <u>logical</u> port as an egress port, <u>said particular port being selected from among available logical ports</u>, said particular <u>logical</u> port being selected for a particular frame of said frames exiting said switch

- (Original) The method of claim 6, wherein applying a pseudo-random process comprises applying a hash function.
- 8. (Currently Amended) The method of claim 6, wherein said correspondence is employed to determine the physical port to which to route said particular frame based at least in part on the logical port selected as said particular <u>logical</u> port.
- 9. (Currently Amended) The method of claim 31, wherein said balancing comprises applying a pseudo-random process to select a particular <u>logical</u> port as an egress port, said particular <u>port being selected from among available logical ports</u>, said particular <u>logical</u> port being selected for each particular frame of said frames exiting said switch.
- 10. (Original) The method of claim 9, wherein applying a pseudo-random process comprises applying a hash function.
- 11. (Currently Amended) The method of claim 9, wherein said correspondence is employed to determine the physical port to which to route each of said particular frames based at least in part on the logical port selected for each of said particular logical ports.
- 12. (Currently Amended) The method of claim 1, wherein said balancing comprises applying weights to select a particular <u>logical</u> port of said switch as an egress port for a particular frame of said frames exiting said switch, said particular port being selected from among available <u>logical</u> ports of said switch.

- 13. (Original) The method of claim 12, wherein said correspondence is employed to determine the physical port to which to route said particular frame based at least in part on the selected logical port.
- 14. (Original) The method of claim 1, wherein a selected physical port for at least one of said frames exiting said switch comprises, for each of said frames exiting said switch, a physical port being selected based at least in part on said correspondence.
- 15. (Currently Amended) The method of claim 14, wherein said balancing comprises applying weights to select a particular <u>logical</u> port of said switch as an egress port for each of said frames exiting said switch, said particular port being selected from among available logical ports of said switch.
- 16. (Currently Amended) The method of claim 15, wherein said correspondence is employed to determine the physical port corresponding to each of said particular <u>logical</u> ports to which to route each of said frames exiting said switch, said corresponding physical port being based at least in part on the logical port selected as the particular <u>logical</u> port.
- 17. (Original) The method of claim 1, wherein a selected physical port for at least one of said frames exiting said switch is further selected based at least in part on a source tag and/or a destination tag added to said frame after said frame enters said switch.
- 18. (Original) The method of claim 17, wherein said source tag and/or said destination tag is stripped off said frame before said frame exits said switch.
- 19. (Original) The method of claim 1, wherein a selected physical port for each of said frames exiting said switch is further selected based at least in part on a source tag and/or a destination tag added to each of said frames after said frames enter, said switch.

- 20. (Original) The method of claim 19, wherein said source tag and/or said destination tag is stripped off each of said frames before each of said frames exits said switch
- 21. (Currently Amended) An apparatus comprising:
 a switch, said switch including a processor and memory;
 said switch further including a <u>plurality of logical</u> and a <u>plurality of physical</u>
 ports, and having the capability to route a flow of frames exiting said switch;

said switch being adapted to apply a correspondence between at least some of said plurality of logical ports and said plurality of physical ports of said switch, at least one logical port having corresponded a plurality of physical ports to form a trunked group, wherein said corresponded physical ports can be any of said plurality of physical ports exiting said switch and wherein frames in a trunked group are delivered in order, and being further adapted to balance frame traffic through said switch using said plurality of logical ports, said frame traffic including frames exiting said switch via said physical ports, a selected physical port for at least one of said frames exiting said switch being selected based at least in part on said correspondence, with any frames exiting said switch via physical ports forming a trunked group being balanced over said physical ports forming the trunked group.

22. (Original) The apparatus of claim 21, wherein said switch is adapted to select a physical port for each of said frames exiting said switch based at least in part on said correspondence.

23.-25. (Cancelled)

26. (Currently Amended) The apparatus of claim 2321, wherein said switch is adapted to balance frame traffic by applying a pseudo-random process to select a particular logical port as an egress port, said particular port being selected from among

available logical ports, said particular <u>logical</u> port being selected for a particular frame of said frames exiting said switch.

- 27. (Original) The apparatus of claim 26, wherein said switch is adapted to apply a pseudo-random process that comprises applying a hash function.
- 28. (Original) The apparatus of claim 26, wherein said switch is adapted to apply said correspondence to determine the physical port to which to route said particular frame based at least in part on the logical port selected as said particular port.
- 29. (Currently Amended) The apparatus of claim 2321, wherein said switch is adapted to apply a pseudo-random process to select a particular <u>logical</u> port as an egress port, said particular <u>port being selected from among available logical ports</u>, said particular <u>logical</u> port being selected for each particular frame of said frames exiting said switch.
- 30. (Original) The apparatus of claim 29, wherein said switch is adapted to apply a pseudo-random process that comprises applying a hash function.
- 31. (Currently Amended) The apparatus of claim 29, wherein said switch is adapted to employ said correspondence to determine the physical port to which to route each of said particular frames based at least in part on the logical port selected for each of said particular logical ports.
- 32. (Currently Amended) The apparatus of claim 21, wherein said switch is adapted to apply weights to select a particular <u>logical</u> port of said switch as an egress port for a particular frame of said frames exiting said switch, said particular port being selected from amone available logical ports of said switch.

33. (Original) The apparatus of claim 32, wherein said switch is adapted to employ said correspondence to determine the physical port to which to route said particular frame based at least in part on the selected logical port.

34. (Original) The apparatus of claim 21, wherein said switch is adapted to select a physical port for at least one of said frames exiting said switch, said physical port being selected based at least in part on said correspondence.

35. (Currently Amended) The apparatus of claim 34, wherein said switch is adapted to apply weights to select a particular <u>logical</u> port of said switch as an egress port for each of said frames exiting said switch, said particular port being selected from among available <u>logical</u> ports of said switch.

36. (Currently Amended) The apparatus of claim 35, wherein said switch is adapted to employ said correspondence to determine the physical port corresponding to each of said particular <u>logical</u> ports to which to route each of said frames exiting said switch, said corresponding physical port being based at least in part on the logical port selected as the particular logical port.

37. (Original) The apparatus of claim 21, wherein said switch is adapted to selected a physical port for at least one of said frames exiting said switch based at least in part on a source tag and/or a destination tag added to said frame after said frame enters said switch.

38. (Original) The apparatus of claim 37, wherein said switch is adapted to strip said source tag and/or said destination tag off said frame before said frame exits said switch.

39. (Original) The apparatus of claim 21, wherein said switch is adapted to select a physical port for each of said frames exiting said switch based at least in part on a

source tag and/or a destination tag added to each of said frames after said frames enter said switch

40. (Original) The apparatus of claim 39, wherein said switch is adapted to strip said source tag and/or said destination tag off each of said frames before each of said frames exits said switch.

41. (Currently Amended) A switch fabric comprising: at least a first switch and a second switch; said first switch including a processor and memory;

said first switch further including a <u>plurality of logical ports</u> and <u>a plurality of</u>
physical ports, and having the capability to route a flow of frames exiting said first
switch:

said first switch being adapted to apply a correspondence between at least some of said plurality of logical ports and said plurality of physical ports, at least one logical port having corresponded a plurality of physical ports to form a trunked group, wherein said corresponded physical ports can be any of said plurality of physical ports exiting said switch and wherein frames in a trunked group are delivered in order, and being further adapted to balance frame traffic through said first switch using said plurality of logical ports, said frame traffic including frames exiting said first switch via said physical ports, a selected physical port for at least one of said frames exiting said first switch being selected based at least in part on said correspondence, with any frames exiting said switch via physical ports forming a trunked group being balanced over said physical ports forming the trunked group.

42. (Original) The switch fabric of claim 41, wherein said first switch is adapted to select a physical port for each of said frames exiting said first switch based at least in part on said correspondence.

43.-45. (Cancelled)

- 46. (Currently Amended) The switch fabric of claim 4341, wherein said first switch is adapted to balance frame traffic by applying a pseudo-random process to select a particular logical port as an egress port, said particular port being selected from among available logical ports, said particular logical port being selected for a particular frame of said frames exiting said first switch.
- 47. (Original) The switch fabric of claim 46, wherein said first switch is adapted to apply a pseudo-random process that comprises applying a hash function.
- 48. (Original) The switch fabric of claim 46, wherein said first switch is adapted to apply said correspondence to determine the physical port to which to route said particular frame based at least in part on the logical port selected as said particular port.
- 49. (Currently Amended) The switch fabric of claim 4341, wherein said first switch is adapted to apply a pseudo-random process to select a particular <u>logical</u> port as an egress port, said particular <u>port being selected from among available logical ports</u>, said particular <u>logical</u> port being selected for each particular frame of said frames exiting said first switch.
- 50. (Original) The switch fabric of claim 49, wherein said first switch is adapted to apply a pseudo-random process that comprises applying a hash function.
- 51. (Currently Amended) The switch fabric of claim 49, wherein said first switch is adapted to employ said correspondence to determine the physical port to which to route each of said particular frames based at least in part on the logical port selected for each of said particular logical ports.
- 52. (Currently Amended) The switch fabric of claim 51, wherein said first switch is adapted to apply weights to select a particular logical port of said first switch as

an egress port for a particular frame of said frames exiting said first switch, said

particular port being selected from among available logical ports of said first switch.

- 53. (Original) The switch fabric of claim 52, wherein said first switch is adapted to employ said correspondence to determine the physical port to which to route said particular frame based at least in part on the selected logical port.
- 54. (Original) The switch fabric of claim 41, wherein said first switch is adapted to select a physical port for at least one of said frames exiting said first switch, said physical port being selected based at least in part on said correspondence.
- 55. (Currently Amended) The switch fabric of claim 54, wherein said first switch is adapted to apply weights to select a particular <u>logical</u> port of said first switch as an egress port for each of said frames exiting said first switch, said particular port being selected from among available <u>logical</u> ports of said first switch.
- 56. (Currently Amended) The switch fabric of claim 55, wherein said first switch is adapted to employ said correspondence to determine the physical port corresponding to each of said particular <u>logical</u> ports to which to route each of said frames exiting said first switch, said corresponding physical port being based at least in part on the logical port selected as the particular <u>logical</u> port.
- 57. (Original) The switch fabric of claim 41, wherein said first switch is adapted to selected a physical port for at least one of said frames exiting said first switch based at least in part on a source tag and/or a destination tag added to said frame after said frame enters said first switch.
- 58. (Original) The switch fabric of claim 57, wherein said first switch is adapted to strip said source tag and/or said destination tag off said frame before said frame exits said first switch.

- 59. (Original) The switch fabric of claim 41, wherein said first switch is adapted to selected a physical port for each of said frames exiting said first switch based at least in part on a source tag and/or a destination tag added to each of said frames after said frames enter said first switch.
- 60. (Original) The switch fabric of claim 59, wherein said first switch is adapted to strip said source tag and/or said destination tag off each of said frames before each of said frames exits said first switch.
 - 61. (Currently Amended) A network comprising:
 - a host:
 - a physical storage unit;
- a first switch and a second switch communicatively coupled to form a switch fabric:

said first switch and said second switch further communicatively coupled to said host and said physical storage unit;

said first switch including a processor and memory, and further including a <u>plurality of logical ports and a plurality of physical ports</u>;

said first switch being adapted to apply a correspondence between at least some of said plurality of logical ports and said plurality of physical ports, at least one logical port having corresponded a plurality of physical ports to form a trunked group, wherein said corresponded physical ports can be any of said plurality of physical ports exiting said switch and wherein frames in a trunked group are delivered in order, and being further adapted to balance frame traffic through said first switch using said plurality of logical ports, said frame traffic including frames exiting said first switch via said physical ports, a selected physical port for at least one of said frames exiting said first switch being selected based at least in part on said correspondence, with any frames exiting said switch via physical ports forming a trunked group being balanced over said physical ports forming the trunked group.

62. (Original) The network of claim 61, wherein said first switch is adapted to select a physical port for each of said frames exiting said first switch based at least in part on said correspondence.

63.-65. (Cancelled)

- 66. (Currently Amended) The network of claim 6361, wherein said first switch is adapted to balance frame traffic by applying a pseudo-random process to select a particular <u>logical</u> port as an egress port, said particular port being selected from among available <u>logical</u> ports, said particular <u>logical</u> port being selected for a particular frame of said frames exiting said first switch.
- 67. (Original) The network of claim 66, wherein said first switch is adapted to apply a pseudo-random process that comprises applying a hash function.
- 68. (Original) The network of claim 66, wherein said first switch is adapted to apply said correspondence to determine the physical port to which to route said particular frame based at least in part on the logical port selected as said particular port.
- 69. (Currently Amended) The network of claim 6361, wherein said first switch is adapted to apply a pseudo-random process to select a particular logical port as an egress port, said particular port-being selected from among available logical ports, said particular logical port being selected for each particular frame of said frames exiting said first switch.
- 70. (Original) The network of claim 69, wherein said first switch is adapted to apply a pseudo-random process that comprises applying a hash function.

- 71. (Currently Amended) The network of claim 69, wherein said first switch is adapted to employ said correspondence to determine the physical port to which to route each of said particular frames based at least in part on the logical port selected for each of said particular logical ports.
- 72. (Currently Amended) The network of claim 61, wherein said first switch is adapted to apply weights to select a particular <u>logical</u> port of said first switch as an egress port for a particular frame of said frames exiting said first switch, said particular port being selected from among available <u>logical ports of said first switch</u>.
- 73. (Original) The network of claim 72, wherein said first switch is adapted to employ said correspondence to determine the physical port to which to route said particular frame based at least in part on the selected logical port.
- 74. (Original) The network of claim 61, wherein said first switch is adapted to select a physical port for at least one of said frames exiting said first switch, said physical port being selected based at least in part on said correspondence.
- 75. (Currently Amended) The network of claim 74, wherein said first switch is adapted to apply weights to select a particular <u>logical</u> port of said first switch as an egress port for each of said frames exiting said first switch, said particular port being selected from among available <u>logical</u> ports of said first switch.
- 76. (Currently Amended) The network of claim 75, wherein said first switch is adapted to employ said correspondence to determine the physical port corresponding to each of said particular <u>logical</u> ports to which to route each of said frames exiting said first switch, said corresponding physical port being based at least in part on the logical port selected as the particular logical port.

77. (Original) The network of claim 61, wherein said first switch is adapted to selected a physical port for at least one of said frames exiting said first switch based at least in part on a source tag and/or a destination tag added to said frame after said frame enters said first switch

78. (Original) The network of claim 77, wherein said first switch is adapted to strip said source tag and/or said destination tag off said frame before said frame exits said first switch

79. (Original) The network of claim 61, wherein said first switch is adapted to selected a physical port for each of said frames exiting said first switch based at least in part on a source tag and/or a destination tag added to each of said frames after said frames enter said first switch

80. (Original) The network of claim 79, wherein said first switch is adapted to strip said source tag and/or said destination tag off each of said frames before each of said frames exits said first switch.

81. (Currently Amended) An article comprising: a storage medium having stored thereon instructions, that when executed, result in performance of a method of routing a flow of frames comprising:

applying a correspondence between a <u>plurality of</u> logical ports and <u>a plurality of</u> physical ports of a switch, <u>at least one logical port having corresponded a plurality of</u> physical ports to form a trunked group, wherein said corresponded physical ports can be any of said plurality of physical ports exiting said switch and wherein frames in a trunked group are delivered in order;

balancing frame traffic through said switch using said plurality of logical ports, said frame traffic including frames exiting said switch via said physical ports, a selected physical port for at least one of said frames exiting said switch being selected based at least in part on said correspondence, with any frames exiting said switch via physical

ports forming a trunked group being balanced over said physical ports forming the trunked group.

82. (Original) The article of claim 81, wherein said instructions, when further executed, result in: a selected physical port for each of said frames exiting said switch being selected based at least in part on said correspondence.

83.-85. (Cancelled)

- 86. (Currently Amended The article of claim 8381, wherein said instructions, when further executed, result in: said balancing comprising applying a pseudo-random process to select a particular <u>logical</u> port as an egress port, said particular <u>port being</u> selected from among available <u>logical</u> ports, said particular <u>logical</u> port being selected for a particular frame of said frames exiting said switch.
- 87. (Original) The article of claim 86, wherein said instructions, when further executed, result in: said applying a pseudo-random process comprising applying a hash function
- 88. (Currently Amended) The article of claim 86, wherein said instructions, when further executed, result in: said correspondence being employed to determine the physical port to which to route said particular frame based at least in part on the logical port selected as said particular <u>logical</u> port.
- 89. (Currently Amended) The article of claim 8381, wherein said instructions, when further executed, result in: said balancing comprising applying a pseudo-random process to select a particular <u>logical</u> port as an egress port, said particular <u>port being</u> selected from among available <u>logical</u> ports, said particular <u>logical</u> port being selected for each particular frame of said frames exiting said switch.

90. (Original) The article of claim 89, wherein said instructions, when further executed, result in: said applying a pseudo-random process comprising applying a hash function

- 91. (Currently Amended) The article of claim 89, wherein said instructions, when further executed, result in: said correspondence being employed to determine the physical port to which to route each of said particular frames based at least in part on the logical port selected for each of said particular logical ports.
- 92. (Currently Amended) The article of claim 91, wherein said instructions, when further executed, result in: said balancing comprising applying weights to select a particular <u>logical</u> port of said switch as an egress port for a particular frame of said frames exiting said switch, said particular port being selected from among available <u>logical ports of said switch</u>.
- 93. (Original) The article of claim 92, wherein said instructions, when further executed, result in: said correspondence being employed to determine the physical port to which to route said particular frame based at least in part on the selected logical port.
- 94. (Original) The article of claim 81, wherein said instructions, when further executed, result in: a selected physical port for at least one of said frames exiting said switch comprising, for each of said frames exiting said switch, a physical port being selected based at least in part on said correspondence.
- 95. (Currently Amended) The article of claim 94, wherein said instructions, when further executed, result in: said balancing comprising applying weights to select a particular <u>logical</u> port of said switch as an egress port for each of said frames exiting said switch, said particular port being selected from among available logical ports of said switch.

- 96. (Currently Amended) The article of claim 95, wherein said instructions, when further executed, result in: said correspondence being employed to determine the physical port corresponding to each of said particular <u>logical</u> ports to which to route each of said frames exiting said switch, said corresponding physical port being based at least in part on the logical port selected as the particular <u>logical</u> port.
- 97. (Original) The article of claim 81, wherein said instructions, when further executed, result in: a selected physical port for at least one of said frames exiting said switch being further selected based at least in part on a source tag and/or a destination tag added to said frame after said frame enters said switch.
- 98. (Original) The article of claim 97, wherein said instructions, when further executed, result in: said source tag and/or said destination tag being stripped off said frame before said frame exits said switch
- 99. (Original) The article of claim 81, wherein said instructions, when further executed, result in: a selected physical port for each of said frames exiting said switch being further selected based at least in part on a source tag and/or a destination tag added to each of said frames after said frames enter said switch.
- 100. (Original)The article of claim 99, wherein said instructions, when further executed, result in: said source tag and/or said destination tag being stripped off each of said frames before each of said frames exits said switch.
- 101. (Currently Amended) An article comprising: a storage medium having stored thereon instructions that, when executed, result in performance of a method of initializing a switch to route a flow of frames comprising:

initializing a correspondence between at least some a plurality of logical ports and a plurality of physical ports of said switch, at least one logical port having corresponded a plurality of physical ports to form a trunked group, wherein said corresponded physical

ports can be any of said plurality of physical ports exiting said switch and wherein frames in a trunked group are delivered in order; and

further initializing said switch to balance frame traffic through said switch <u>using</u> said plurality of logical ports, said frame traffic including frames exiting said switch via said physical ports, a selected physical port for at least one of said frames exiting said switch being selected based at least in part on said correspondence, <u>with any frames</u> exiting said switch via physical ports forming a trunked group being balanced over said physical ports forming the trunked group.

102. (Cancelled)

- 103. (Currently Amended) The article of claim 100, wherein said instructions, when further executed, result in: initializing said switch to balance frame traffic by applying a pseudo-random process to select a particular logical port as an egress port, said particular port being selected from among available logical ports, said particular logical port being selected for a particular frame of said frames exiting said switch.
- 104. (Currently Amended) The article of claim 103, wherein said instructions, when further executed, result in: initializing said switch to apply a pseudo-random process to select a particular <u>logical</u> port as an egress port, said particular <u>port being</u> selected from among available <u>logical ports</u>, said particular <u>logical</u> port being selected for each particular frame of said frames exiting said switch.
- 105. (Currently Amended) The article of claim 100, wherein said instructions, when further executed, result in: initializing said switch to balance frame traffic by applying weights to select a particular logical port of said switch as an egress port for a particular frame of said frames exiting said switch, said particular port being selected from amone available logical ports of said switch.